



TRANSFORMERS MAGAZINE'S
INDUSTRY NAVIGATOR

SUSTAINABILITY AND DIGITALIZATION

Condition Monitoring of Power Transformer Insulation: HV Bushings, Partial Discharges and Transient Overvoltages

Vedran Jerbić,
Principal Engineer
Končar – Electrical Engineering Institute


June 2023





Purpose of Condition monitoring


- To detect emerging faults
- To enable condition-based maintenance
- To provide optimum transformer management
- To improve personnel and environment safety
- To enhance fault cause analysis





Insulation Monitoring Methods


- Bushing Monitoring
 - Capacitance C1
 - Dissipation Factor
- Transients Overvoltage Monitoring
 - Estimation of insulation stress
 - Grid modelling
- Partial Discharges Measurements and Monitoring
 - Apparent Charge
 - PRPD map used for pinpointing the cause
 - Localization of PD source





Bushing Monitoring methods


- 3phase bank methods
 - Sum of currents
 - Adjacent Phase to Phase
 - Advantages:
 - Simple method
 - Less cabling
 - High sensitivity
 - Disadvantages:
 - Network unbalance problems
- VT reference method
 - Advantages:
 - Absolute measurement
 - No network unbalance problems
 - Faster response
 - Disadvantages:
 - More cabling
- Dual transformer method
 - Advantages:
 - Monitors 6 bushings
 - No network unbalance problems
 - Faster response
 - Disadvantages:
 - More cabling





Case – power plant for peak loading

- Power plant information
 - Hydro power plant commonly used during peak loading
 - 3 generators
 - 3 step-up transformers (3-phase 25MVA)
 - Transformers connected to same 110 kV busbar
- Challenges
 - 3Phase bank method cannot be used since transformers are rarely on the grid more than a few days and averaging cannot be used to overcome grid imbalance
 - Reference methods must be used
 - Data sharing and synchronization of distributed measurements
- Monitoring topology
 - 3 distributed TMS cubicles
 - Connected to the same LAN
 - Each TMS shares measurements with others
 - Each is synchronized to the same time
 - No added complexity and additional expenses
 - Additional feature monitoring of fast transients





Compensation method

- High sensitivity measurements
 - Each device measures bushing leakage currents amplitude and phase angle
 - Phase angle accuracy must be better than 0.01°
 - Leakage current amplitude and phase angle depends on:
 - Bushing C1 capacitance and dissipation factor
 - Grid voltage and phase angles
- HOW IS IT DONE?
 - Grid errors compensated using simple subtractions

$$\frac{\Delta C_{measured}}{C_0} = \frac{\Delta C_{real}}{C_0} + CAP_ERR_{GRID}$$

$$\Delta tg\delta_{measured} = \Delta tg\delta_{real} + TG_ERROR_{GRID}$$

$$\frac{\Delta C}{C_0} = \frac{\Delta C_{DUT}}{C_0} - \frac{\Delta C_{REF}}{C_0}$$

$$\Delta tg\delta = \Delta tg\delta_{DUT} - \Delta tg\delta_{ref}$$







Example - Installation

- OIP Bushings
 - Same Type and Manufacturer on all transformers
 - Periodically checked using offline methods
 - Monitoring installed in 2020



	AT1	AT2	AT3
Phase U	2017	2004	2004
Phase V	1999	2004	2004
Phase W	1999	2004	2004







Example – Lightning strikes recorded

- Transient Recorder Performance
 - 4 - 16 channels @ 5 MSps
 - Rise times > 350 ns
 - Long acquisition time, up to 7 seconds
 - Synchronized time
- Transient recorder benefits
 - Overvoltage protection monitoring
 - Overvoltage mapping
 - Insulation stresses assessment
 - Comparison with standard testing impulses
 - Non-standard impulses







Example - Monitoring Results





Postmortem analysis – dissipation factor


- Dissipation factor temperature dependency
 - Saddle-like curve
 - Curve shape depends on moisture
- Testing faulty bushing in climatic chamber
 - Comparison with manufacturer's data
 - Testing in the range from 0 – 80 °C
- Conclusion
 - Monitoring measurement confirmed





Postmortem analysis - PD

- Insulation deterioration can be assessed by measuring PD
- Testing faulty bushing in a high voltage lab
- Partial discharges appearance





THANK YOU FOR YOUR ATTENTION

www.koncar-institut.com

